Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in

the application:

44. (Currently Amended) A method implemented in a subscriber unit,

wherein a multicast group comprises a plurality of subscriber units, the method

comprising:

receiving a multicast group paging indication message via a first one of a

plurality of wireless channels, the multicast group paging indication message

indicating identifying a connection identifier associated with a multicast message,

wherein the connection identifier indicates a second one of the plurality of wireless

channels over which to receive a the multicast message that is associated with at

least one connection identifier.

45. (Currently Amended) The method of claim 44, further comprising:

receiving the multicast message via the indicated second one of the plurality

of wireless channels

- 2 -

Applicant: Farley et al. Application No.: 09/630,024

46. (Currently Amended) The method of claim 44 further comprising:

receiving the multicast message concurrently with other subscriber units in

the multicast group.

47. (Previously Presented) The method of claim 44 wherein the second

one of the plurality of wireless channels is a dedicated channel.

48. (Currently Amended) The method of claim 44 wherein only a

subscriber unit associated with the multicast group decodes the multicast message

transmitted received over the second wireless channel.

49. (Currently Amended) A method of transmitting multicast

messages, wherein a multicast group comprises a plurality of subscriber units, the

method comprising:

transmitting a multicast group paging indication message via a first one of a

plurality of wireless channels, the multicast group paging indication message

indicating identifying a connection identifier associated with a multicast message,

wherein the connection identifier indicates a second one of the plurality of wireless

channels over which a corresponding multicast message associated with at least one

connection identifier will be transmitted; and

- 3 -

transmitting the multicast message  $\underline{\text{to the multicast group}}$  via the second one

of the plurality of wireless channels.

50. (Currently Amended) The method of claim 49 further comprising:

transmitting the multicast message via the indicated second one of the

plurality of wireless channels.

51. (Currently Amended) The method of claim 49 further comprising:

performing a lookup in a routing table adapted to store entries associating a

multicast group with a  $\underline{\text{the}}$  connection identifier; and

performing a lookup in a table adapted to associate the connection identifier

with the at least one subscriber unit.

52. (Previously Presented) The method of claim 49 further comprising:

receiving a join group request from a subscriber unit; and

adding an entry in the table indicative of an association between the

multicast group and the subscriber unit.

53. (Previously Presented) The method of claim 49 further comprising:

scanning the multicast message; and

parsing a group address in response to a determination that the multicast

message is directed to the multicast group.

54. (Previously Presented) The method of claim 53 wherein the group

address conforms to a protocol and the multicast message is parsed in accordance

with the protocol.

55. (Previously Presented) The method of claim 54 wherein the protocol

is the Internet Group Management Protocol (IGMP).

56. (Previously Presented) The method of claim 49 wherein the first one

of the plurality of wireless channels is a dedicated channel.

57. (Previously Presented) The method of claim 49 further comprising:

receiving a negative acknowledgment from a subscriber unit associated with

the multicast group; and

retransmitting the multicast message.

58. (Canceled)

- 5 -

Applicant: Farley et al. Application No.: 09/630,024

59. (Currrently Amended) A subscriber unit comprising:

a receiver configured to

receive a multicast group paging indication message via a first one of a plurality of wireless channels, the multicast group indication message identifying a connection identifier associated with a multicast message, therein the connection identifier indicates indicating a second one of the plurality of wireless channels over which to receive a corresponding multicast message associated with at least one connection identifier; and

receive the multicast message via the second one of the plurality of wireless channels.

60. - 61. (Canceled)

 (Previously Presented) The subscriber unit of claim 59 wherein the second one of the plurality of wireless channels is a dedicated channel.

63. (Canceled)

64. (Currently Amended) A base station for multicasting messages, the base station comprising: a processor configured to receive a multicast message addressed to a

multicast group having two or more subscriber units;

a transmitter configured to

transmit a multicast group paging indication message to a multicast

group via a first one of a plurality of wireless channels, the multicast group paging

indication message identifying a connection identifier associated with a multicast

message, wherein the connection identifier indicates indicating a second one of the

plurality of wireless channels over which a corresponding multicast message

associated with at least one connection identifier will be transmitted; and

transmit the multicast message via the second one of the plurality of

wireless channels.

65. (Canceled)

66. (Currently Amended) The base station of claim 64 wherein:

the processor is further configured to perform a lookup in a routing table

adapted to store entries associating a multicast group with a the connection

identifier; and to perform a lookup in a table adapted to associate the connection

identifier with the at least subscriber units.

- 7 -

Applicant: Farley et al. Application No.: 09/630,024

67. (Previously Presented) The base station of claim 66, further

comprising:

a receiver configured to receive a join group request from a subscriber unit;

wherein the processor is further configured to add an entry in the table indicative of an association between the multicast group and the subscriber unit.

68. (Previously Presented) The base station of claim 64 wherein the

processor is further configured to scan the multicast message; and to parse a group

address in response to a determination that the multicast message is directed to the

multicast group.

69. (Previously Presented) The base station of claim 68 wherein the

group address conforms to a protocol and the multicast message is parsed by the

processor in accordance with the protocol.

70. (Previously Presented) The base station of claim 69 wherein the

protocol is the Internet Group Management Protocol (IGMP).

71. (Previously Presented) The base station of claim 70 wherein the first

one of the plurality of wireless channels is a dedicated channel.

- 8 -

Applicant: Farley et al. Application No.: 09/630,024

72. (Previously Presented) The base station of claim 64, further

comprising:

a receiver configured to receive a negative acknowledgment from a subscriber

unit associated with the multicast group;

wherein the transmitter is further configured to retransmit the multicast

message via the second one of the plurality of wireless channels in response to the

negative acknowledgement.

- 9 -